



Refrigerated medical cabinet “Pharmalow” S, L and M

WITH FAN ASSISTED CIRCULATION.
TEMPERATURES RANGE FROM +0 °C UP TO +15 °C.



APPLICATIONS

Products that require a constant below atmosphere temperature, preservation of pharmaceutical products, medications, micro-tubes, etc.

Automatic de-frost with water evaporation system.
Adjustable level, front base supports.
Door can be mounted to open left or right.
Door lock.

COMMON FEATURES

External case and metallic door.
White coated and interior made of anti-toxic white sheet.
Double glazed door and interior light for model M.
Hermetically sealed compressor.
Homogeneous, turbine fan assisted air circulation.

CONTROL PANEL

Temperature thermostat regulator.
Digital thermometer display for models S and L.
Electronic digital temperature control model M.

Refrigerator “Pharmalow” S and L

MODELS	Part No.	Capacity litres	Height / Width / Depth (interior) cm	Height / Width / Depth (exterior)cm	Number of shelves	Power W	Weight Kg
Pharmalow S	2101274	252	105 51 44	121 60 60	4	170	47
Pharmalow L	2101275	352	142 51 44	159 60 60	5	180	62

Comes complete with steel shelves, PVC laminated.

ACCESSORIES Need to be factory fitted.

Frame support, partitioned metallic drawers.

Modular system with perforated base, sliding drawers, each drawer is divided into three fixed compartments, each compartment with four removable methacrylate partitions.

Frame support for Pharmalow S (Part No. 2101274), with 4 drawers and 48 partitions in total, (maximum capacity: 6 drawers).

Part No. **1001306**

Frame support for Pharmalow L (Part No. 2101275), with 5 drawers and 60 partitions in total, (maximum capacity: 10 drawers).

Part No. **1001307**

OPTIONAL

Drawer with 3 compartments and 12 partitions.

Part No. **1001308**



Model Pharmalow S and L with frame support and drawers.



Details of frame support, drawers, dividers and partitions.



Model Pharmalow S with 4 shelves.

NEW DESIGN



Model Pharmalow M with 6 shelves.

Storage refrigerator with double glazed anti mist door “Pharmalow” M

WITH DIGITAL ELECTRONIC TEMPERATURE CONTROL

MODEL

Part No.	Capacity litres	Height / Width / Depth (interior) cm	Alto / Ancho / Fondo (exterior)cm	Power W	Power HP	Number of shelves	Weight Kg
2101501	319	139 48 45	198 60 64	360	1/4	6	98

Comes complete with steel shelves, PVC laminated.

ACCESSORY “Pharmalow” S - L and M. Must be factory fitted.

Circular graphic register independently powered.

Temperature range: -10 °C up to 40 °C. Precision $\pm 2\%$ at 12 °C.

Chart speed selection of 24 hours or 7 days. Disc \varnothing 125mm

Graphic register dimensions:

18 cm high x 22 cm wide x 35 cm deep.

Powered by an LR-6 1.5V battery. Battery life 1 year.

Part No. **2101621**

